



Declaration of Performance
N° 0116300-NOVASIT-K2
PYRO-SAFE NOVASIT K2

Date: 06.02.2017
Rev. 02
Page 1 of 1

Unique identification code of the product-type
PYRO-SAFE NOVASIT K2

Intended use

Standard masonry mortar according to qualification testing for the installation of pipe bulkheads in walls and ceilings as well as joints around fire dampers and fire protection doors.

Manufacturer

svt Brandschutz Vertriebsgesellschaft mbH International
Gluesinger Strasse 86
D - 21217 Seevetal

System or systems of assessment and verification of constancy of performance
System 2+

Harmonised technical specification
EN 998-2: 2010

The Notified body

MPA Bau Hannover, identification number 0764

Declared performance

Table with 3 columns: Essential characteristics, Performance, and Harmonised technical specification. Rows include Reaction to fire (class A1), Pressure resistance (M 20), Starting shear strength (0,3 N/mm²), Water absorption (NPD), Chloride content (≤ 0,10 M.-%), Water vapor permeability (15/35), Thermal conductivity (≤ 0,82 W/(mK)), and Durability (assessment of use provided).

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above. DoP online available at www.svt.de. Signed for and on behalf of the manufacturer by:

Handwritten signature of Christian Meyer-Korte

i.V. Christian Meyer-Korte
Head of Product Management

Handwritten signature of Andree Schober

i.V. Andree Schober
Head of chemical department